# MATERION

# SAFETY DATA SHEET

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of the substance Chromium Selenide (CrSe) **Identification number** 034-002-00-8 (Index number)

Registration number

**Document number** 1HC

Chromium selenide (CrSe) \* Chromium selenide **Synonyms** 

**Materion Code** 

**Issue date** 02-September-2014 **Revision date** 10-January-2018

# 1.3. Details of the supplier of the safety data sheet

**Supplier** 

Company name Materion Advanced Chemicals Inc.

**Address** 407 N. 13th Street

> 1316 W. St. Paul Avenue Milwaukee, WI 53233

United States

**Division** Milwaukee **Telephone** 414.212.0257

e-mail advancedmaterials@materion.com

Contact person Laura Hamilton

1.4. Emergency telephone

number

Supersedes date 06-May-2015

**Version number** 

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Not available. Uses advised against None known.

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

The substance has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

**Health hazards** 

H301 - Toxic if swallowed. Acute toxicity, oral Category 3 Acute toxicity, inhalation Category 3 H331 - Toxic if inhaled. Specific target organ toxicity - repeated Category 2 H373 - May cause damage to exposure organs through prolonged or

repeated exposure.

**Environmental hazards** 

Hazardous to the aquatic environment, acute Category 1 H400 - Very toxic to aquatic life.

aquatic hazard

Hazardous to the aquatic environment, H410 - Very toxic to aquatic life Category 1

long-term aquatic hazard with long lasting effects.

**Hazard summary** Dangerous for the environment if discharged into watercourses.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

**Contains:** Chromium Selenide (CrSe)

#### **Hazard pictograms**



#### Signal word Danger

#### **Hazard statements**

H301 Toxic if swallowed. H331 Toxic if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

#### Prevention

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P261 Avoid breathing dust.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P311 Call a POISON CENTRE/doctor.

P330 Rinse mouth. P391 Collect spillage.

**Storage** 

Store away from incompatible materials.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

**Disposal** 

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label

information

Not applicable.

**2.3. Other hazards** None known.

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

#### **General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Chromium Selenide (CrSe	) 90 - 100	12053-13-3 234-999-1	-	034-002-00-8	#
Classification:	Acute Tox. 3;H301, Acut Aquatic Chronic 1;H410	te Tox. 3;H331, ST	OT RE 2;H373, Aquatic Acute	1;H400,	Α

## List of abbreviations and symbols that may be used above

CLP: Regulation No. 1272/2008.

DSD: Directive 67/548/EEC.

M: M-factor

vPvB: very persistent and very bioaccumulative substance. PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

#### **SECTION 4: First aid measures**

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.

**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

1HC Version #: 03 Revision date: 10-January-2018 Issue date: 02-September-2014

4.2. Most important symptoms and effects, both acute and delayed

Direct contact with eyes may cause temporary irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

# **SECTION 5: Firefighting measures**

**General fire hazards** No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

During fire, gases hazardous to health may be formed.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or

mixture

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special firefighting

procedures

Use water spray to cool unopened containers.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials.

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protective equipment. Ensure adequate ventilation. Local authorities should be

advised if significant spillages cannot be contained.

For emergency responders

Keep unnecessary personnel away.

6.2. Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop the flow of material, if this is without risk. Collect spillage. Prevent product from entering drains. Following product recovery, flush area with water.

6.4. Reference to other

Not available

sections

# 7.1. Precautions for safe

handling

Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains.

7.2. Conditions for safe storage, including any

incompatibilities

Store in original tightly closed container.

Not available. 7.3. Specific end use(s)

**SECTION 7: Handling and storage** 

## **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

#### **Occupational exposure limits**

Austria. MAK List, OEL Ordinano Material	Туре	Value	Form	
Chromium Selenide (CrSe) (CAS 12053-13-3)	STEL	0,3 mg/m3	Inhalable fraction.	
			Form	
	e (GwV), BGBl. II, no. 184/2001 Type	Value	Form	
Austria. TRK List, OEL Ordinance Material  Chromium Selenide (CrSe) (CAS 12053-13-3)		Value 0,4 mg/m3	Form	

Material name: Chromium Selenide (CrSe)

SDS EU 1HC Version #: 03 Revision date: 10-January-2018 Issue date: 02-September-2014

	Туре	Value	Form
	TWA	0,1 mg/m3	
		0,05 mg/m3	Inhalable fraction.
Croatia. Dangerous Substance E	xposure Limit Values in the	Workplace (ELVs), Annexes	1 and 2, Narodne Novinc
13/09 Material	Туре	Value	
Chromium Selenide (CrSe) (CAS 12053-13-3)	MAC	0,1 mg/m3	
Cyprus. OELs. Control of factory	atmosphere and dangerous	substances in factories regu	lation, PI 311/73, as
amended. Material	Туре	Value	
Chromium Selenide (CrSe) (CAS 12053-13-3)	TWA	0,2 mg/m3	
Finland. Workplace Exposure Li		_	
Material	Туре	Value	
Chromium Selenide (CrSe) (CAS 12053-13-3)	STEL	0,3 mg/m3	
France. Threshold Limit Values ( Material	(VLEP) for Occupational Exp Type	osure to Chemicals in France Value	, INRS ED 984
Chromium Selenide (CrSe) (CAS 12053-13-3)	VME	2 mg/m3	
Germany. DFG MAK List (adviso	ry OELs). Commission for th	e Investigation of Health Ha	zards of Chemical
Compounds in the Work Area (E Material	•	Value	Form
Chromium Selenide (CrSe)	Type  TWA	0,02 mg/m3	Inhalable fraction.
(CAS 12053-13-3)	TWA	0,02 1119/1113	Tillalable Haction.
Iceland. OELs. Regulation 154/ Material	1999 on occupational exposi Type	ure limits Value	
Chromium Selenide (CrSe) (CAS 12053-13-3)	TWA	0,1 mg/m3	
	nal exposure limit values (A		
	onal exposure limit values (A Type	nnex I), Memorial A Value	
Material Chromium Selenide (CrSe)	= = = = = = = = = = = = = = = = = = = =		
Material Chromium Selenide (CrSe) (CAS 12053-13-3) Malta. OELs. Occupational Expo	<b>Type</b> TWA	Value 2 mg/m3	Safety Authority Act (CA
Material Chromium Selenide (CrSe) (CAS 12053-13-3) Malta. OELs. Occupational Expo	<b>Type</b> TWA	Value 2 mg/m3	Safety Authority Act (CA
Material Chromium Selenide (CrSe) (CAS 12053-13-3) Malta. OELs. Occupational Exportance 424), Schedules I and V) Material Chromium Selenide (CrSe)	Type  TWA  sure Limit Values (L.N. 227.	Value 2 mg/m3 of Occupational Health and S	Safety Authority Act (CA
Material Chromium Selenide (CrSe) (CAS 12053-13-3) Malta. OELs. Occupational Exportance (A24), Schedules I and V) Material Chromium Selenide (CrSe) (CAS 12053-13-3) Netherlands. OELs (binding)	Type  TWA  sure Limit Values (L.N. 227.  Type	Value 2 mg/m3  of Occupational Health and S  Value	Safety Authority Act (CA
Material Chromium Selenide (CrSe) (CAS 12053-13-3) Malta. OELs. Occupational Exportance (A24), Schedules I and V) Material Chromium Selenide (CrSe) (CAS 12053-13-3) Netherlands. OELs (binding) Material Chromium Selenide (CrSe)	Type  TWA  sure Limit Values (L.N. 227.  Type  TWA	Value 2 mg/m3  of Occupational Health and S  Value 2 mg/m3	Safety Authority Act (CA
Material Chromium Selenide (CrSe) (CAS 12053-13-3) Malta. OELs. Occupational Exportance (A24), Schedules I and V) Material Chromium Selenide (CrSe) (CAS 12053-13-3) Netherlands. OELs (binding) Material Chromium Selenide (CrSe)	Type  TWA  sure Limit Values (L.N. 227.  Type  TWA  Type	Value 2 mg/m3  of Occupational Health and S  Value 2 mg/m3  Value	Safety Authority Act (CA
Luxembourg. Binding Occupation Material  Chromium Selenide (CrSe) (CAS 12053-13-3)  Malta. OELs. Occupational Exponence 424), Schedules I and V) Material  Chromium Selenide (CrSe) (CAS 12053-13-3)  Netherlands. OELs (binding) Material  Chromium Selenide (CrSe) (CAS 12053-13-3)  Portugal. OELs. Decree-Law n. 2  Material	Type  TWA  sure Limit Values (L.N. 227.  Type  TWA  Type  STEL  TWA	Value 2 mg/m3  of Occupational Health and S  Value 2 mg/m3  Value 0,05 mg/m3  0,025 mg/m3	Safety Authority Act (CA
Material Chromium Selenide (CrSe) (CAS 12053-13-3) Malta. OELs. Occupational Expora 424), Schedules I and V) Material Chromium Selenide (CrSe) (CAS 12053-13-3) Netherlands. OELs (binding) Material Chromium Selenide (CrSe) (CAS 12053-13-3) Portugal. OELs. Decree-Law n. 2 Material Chromium Selenide (CrSe)	Type TWA sure Limit Values (L.N. 227. Type TWA  Type STEL TWA 290/2001 (Journal of the Re	Value 2 mg/m3  of Occupational Health and S  Value 2 mg/m3  Value  0,05 mg/m3  0,025 mg/m3  public - 1 Series A, n.266)	Safety Authority Act (CA
Material Chromium Selenide (CrSe) (CAS 12053-13-3) Malta. OELs. Occupational Expora 424), Schedules I and V) Material Chromium Selenide (CrSe) (CAS 12053-13-3) Netherlands. OELs (binding) Material Chromium Selenide (CrSe) (CAS 12053-13-3) Portugal. OELs. Decree-Law n. 2	Type TWA  sure Limit Values (L.N. 227.  Type TWA  Type STEL TWA  290/2001 (Journal of the ReType TWA	Value 2 mg/m3  of Occupational Health and S  Value 2 mg/m3  Value 0,05 mg/m3  0,025 mg/m3  public - 1 Series A, n.266) Value 2 mg/m3	Safety Authority Act (CA

Chromium Selenide (CrSe)  STEL  Q, 2 mg/m3  TWA  Q,1 mg/m3  Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Type  Chromium Selenide (CrSe)  (CAS 12053-13-3)  Spain. Carcinogens and Mutagens with Limit Values (Table 2) Material  Type  Chromium Selenide (CrSe)  Cromium Selenide (CrSe)  Cromium Selenide (CrSe)  TWA  Q,01 mg/m3  Chromium Selenide (CrSe)  Cromium Selenide (CrSe)  Cromium Selenide (CrSe)  Switzerland. SUVA Grenzwerte am Arbeitsplatz  Material  Type  Chromium Selenide (CrSe)  STEL  Q,16 mg/m3  Inhalable dust.  CRS 12053-13-3)  Switzerland. SUVA Grenzwerte in Type  Chromium Selenide (CrSe)  CRS 12053-13-3)  Sullimit values  France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 20 Material  Chromium Selenide (CrSe)  Q,01 mg/g  Chrome total  Chromium Se	0,1 mg/m3 erning protection of health in work with chemical agents Value	5121	
Slovakia, OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Material Type  Chromium Selenide (CrSe) C(AS 12033-13-3)  Spain. Carcinogens and Mutagens with Limit Values (Table 2) Material Type  Chromium Selenide (CrSe) C(AS 12033-13-3)  Switzerland. SUVA Grenzwerte am Arbeitsplatz Material Type  Value  Form  Chromium Selenide (CrSe) C(AS 12033-13-3)  EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU Material Type  Value  EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU Material Type  Value  Form  TWA  2 mg/m3  Inhalable dust. (CAS 12033-13-3)  10gical limit values France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 20 Material)  Value  Determinant Specimen Selenide (CrSe) 0,03 mg/g Chrome total Urine  *- For sampling details, please see the source document.  Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4 Material  Chromium Selenide (CrSe) 25 µg/l Cromo total Urine  *- For sampling details, please see the source document.  Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4 Material  Chromium Selenide (CrSe) 10 µg/l Cromo total Urine  *- For sampling time  Chromium Selenide (CrSe) 10 µg/l Cromo total Urine  *- For sampling time  Chromium Selenide (CrSe) 10 µg/l Cromo total Urine  *- For sampling time  Chromium Selenide (CrSe) 10 µg/l Cromo total Urine  *- For sampling tetalls, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)  Material  Chromium Selenide (CrSe) 10 µg/l Cromo total Urine  *- For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per Suppling Time  Chromium Selenide (CrSe) 10 µg/l Cromo total Urine  *- For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological	erning protection of health in work with chemical agents Value		` ,
Material   Type	Value		
Spain. Carcinogens and Mutagens with Limit Values (Table 2) Material  Chromium Selenide (CrSe) EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU Material Type  Chromium Selenide (CrSe) Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4 Material Value Determinant Specimen Sampling Time  * - For sampling details, please see the source document.  Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4 Material Value Determinant Specimen Sampling Time  * - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA) Material Value Determinant Specimen Selenide (CrSe) Selen Serum  * - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA) Material Value Determinant Specimen Selenide (CrSe) Selen Serum  * - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA) Material Value Determinant Specimen Selenide (CrSe) Selen Serum  * - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)  Material Value Determinant Specimen Selective to an acceptable	0,1 mg/m3		
Naterial   Type		TWA	
Switzerland. SUVA Grenzwerte am Arbeitsplatz Material Type STEL 0,16 mg/m3 Inhalable dust. Chromium Selenide (CrSe) CAS 12053-13-3)  EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU Material Type Value  Chromium Selenide (CrSe) CAS 12053-13-3)  EU. Toldicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU Material Type Value  Chromium Selenide (CrSe) CAS 12053-13-3)  Reference. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 20 Material Value Determinant Specime Sampling Time  Chromium Selenide (CrSe) Reference Spain Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4 Material Value Determinant Specime Sampling Time  Chromium Selenide (CrSe) Reference Spain Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4 Material Urine *  * - For sampling details, please see the source document.  Spain Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4 Material Urine *  * - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA) Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe)  Reference Refect Levels  William Selenide (CrSe) Reference Refect Reference Refer		<del>-</del>	<del>-</del>
Material Type	0,01 mg/m3	TWA	
EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU Material Type Value  Chromium Selenide (CrSe) (CAS 12053-13-3)  Diogical limit values  France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 20 Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe) 0,03 mg/g Chrome total Creatinine in wirne  * - For sampling details, please see the source document.  Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4 Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe) 25 µg/l Cromo total Urine *  * - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA) Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe) 150 µg/l Selen Serum *  * - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA) Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe) 150 µg/l Selen Serum *  * - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA) Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe) 150 µg/l Selen Serum *  * - For sampling details, please see the source document.  Commended monitoring occidures.  Commended monitoring Follow standard monitoring procedures.  Commended monitoring of Sood general ventilation (typically 10 air changes per hour) should be used. Ventilation to be matched to conditions. If applicable, use process enclosures, local exhaust ventilation engineering controls to maintain air/borne levels below recommended exposure limits. If limits have not been established, maintain airborne levels below recommended exposure limits. If limits have not been established, maintain airborne levels below recommended exposure limits. If limits have not bee		-	
Material Type Value  Chromium Selenide (CrSe) (CAS 12053-13-3)  Dological limit values  France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 20 Material Value Determinant Specime Sampling Time  Chromium Selenide (CrSe) (CAS 12053-13-3)  0,01 mg/g Chrome total Creatinine in * urine  * - For sampling details, please see the source document.  Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4 Material Value (CRS 12053-13-3)  10 µg/l Cromo total Urine *  * - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)  Material Value Determinant Specime Sampling Time  Chromium Selenide (CrSe) (CAS 12053-13-3)  10 µg/l Selen Serum *  * - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)  Material Selenide (CrSe) (CAS 12053-13-3)  * - For sampling details, please see the source document.  Chromium Selenide (CrSe) (CAS 12053-13-3)  * - For sampling details, please see the source document.  Commended monitoring controls of the standard monitoring procedures.  Follow standard monitoring procedures.  Commended monitoring controls to maintain anithorne levels below recommended exposure limits. If limits have not been established, maintain airborne levels below recommended exposure limits. If limits have not been established, maintain airborne levels below recommended exposure limits. If limits have not been established, maintain airborne levels below recommended exposure limits. If limits have not been established, maintain airborne levels below recommended exposure limits. If limits have not been established, maintain airborne levels below recommended exposure limits. If limits have not been established, maintain airborne levels below recommended exposure limits. If limits have not been established, maintain airborne levels below recommended exposure limits. If limits have	0,16 mg/m3 Inhalable dust.	STEI	
CAS 12053-13-3   Pological limit values   Prance. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 20 Material Value Determinant Specimen Sampling Time   Prancisco			<del>-</del>
France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 20 Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe) 0,03 mg/g Chrome total Creatinine in winne urine 0,01 mg/g Chrome total Creatinine in winne winne with urine 1 winne 2	2 mg/m3	TWA	
Material         Value         Determinant         Specimen         Sampling Time           Chromium Selenide (CrSe) (CAS 12053-13-3)         0,01 mg/g         Chrome total         Creatinine in urine         * urine           * - For sampling details, please see the source document.         Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4           Material         Value         Determinant         Specimen         Sampling Time           Chromium Selenide (CrSe)         25 μg/l         Cromo total         Urine         *           Chromium Selenide (CrSe)         25 μg/l         Cromo total         Urine         *           * - For sampling details, please see the source document.         Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)         Sampling Time           Chromium Selenide (CrSe)         150 μg/l         Selen         Serum         *           Commended monitoring redures         Follow standard monitoring procedures         *         *           Selicited			logical limit values
(CAS 12053-13-3)  0,01 mg/g Chrome total Creatinine in urine  * - For sampling details, please see the source document.  Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4  Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe) (CAS 12053-13-3)  10 μg/l Cromo total Urine  * - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)  Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe) (CAS 12053-13-3)  * - For sampling details, please see the source document.  Chromium Selenide (CrSe) (CAS 12053-13-3)  * - For sampling details, please see the source document.  Chromium Selenide (CrSe) (CAS 12053-13-3)  * - For sampling details, please see the source document.  Follow standard monitoring procedures.  Commended monitoring Conductor (PNECs)  Commended monitoring Conductor (PNECs)  Commended monitoring Conductor (PNECs)  Commended monitoring Conductor (PNECs)  Con		-	<del>-</del>
* - For sampling details, please see the source document.  Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4  Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe) 25 µg/l Cromo total Urine *  * - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)  Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe) 150 µg/l Selen Serum *  (CAS 12053-13-3)  * - For sampling details, please see the source document.  Commended monitoring coedures  rived no effect levels with the commended monitoring procedures.  Selicited no effect levels with the commended monitoring of the commended monitoring propriate engineering and the matched to conditions. If applicable, use process enclosures, local exhaust ventilation engineering controls to maintain airborne levels below recommended exposure limits. If applicable in the commended exposure limits, if applicable in the commended exposure limits. If applicable in the commended exposure limits have not been established, maintain airborne levels to an acceptable level.  Ilividual protection measures, such as personal protective equipment  General information Personal protection equipment should be chosen according to the CEN standards and in the commended exposure in	Chrome total Creatiline in	0,03 mg/g	
Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4         Material         Value         Determinant         Specimen         Sampling Time           Chromium Selenide (CrSe) (CAS 12053-13-3)         25 μg/l         Cromo total         Urine         *           * - For sampling details, please see the source document.         Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)         Sampling Time           Chromium Selenide (CrSe) (CAS 12053-13-3)         150 μg/l         Selen         Serum         *           * - For sampling details, please see the source document.         commended monitoring occluses         Follow standard monitoring procedures.           commended monitoring occluses         Follow standard monitoring procedures.         Follow standard monitoring procedures.           centrations (PNECs)         Not available.           Exposure controls occluses         Not available.           Good general ventilation (typically 10 air changes per hour) should be used. Ventilation or be matched to conditions. If applicable, use process enclosures, local exhaust ventilation engineering controls to maintain airborne levels below recommended exposure limits. If alimits have not been established, maintain airborne levels to an acceptable level.           dividual protection measures, such as personal protective equipment         Personal protection equipment should be chosen according to the CEN standards and in the conditions.	chiome total — Creatimie in	0,01 mg/g	
Material         Value         Determinant         Specimen         Sampling Time           Chromium Selenide (CrSe) (CAS 12053-13-3)         25 μg/l         Cromo total         Urine         *           * - For sampling details, please see the source document.         *         *           Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)         Sampling Time           Chromium Selenide (CrSe)         150 μg/l         Selen         Serum         *           Chromium Selenide (CrSe) (CAS 12053-13-3)         150 μg/l         Selen         Serum         *           * - For sampling details, please see the source document. commended monitoring procedures.         Follow standard monitoring procedures.           commended monitoring occlures         Follow standard monitoring procedures.           rived no effect levels intended for the controls of the control of	ent.	ease see the source doc	* - For sampling details, ple
(CAS 12053-13-3)  10 μg/l Cromo total Urine *  * - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)  Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe) 150 μg/l Selen Serum *  (CAS 12053-13-3)  * - For sampling details, please see the source document.  commended monitoring procedures  rived no effect levels NELs)  Pedicted no effect ncentrations (PNECs)  Exposure controls propriate engineering introls  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation regineering controls to maintain airborne levels below recommended exposure limits. If a limits have not been established, maintain airborne levels to an acceptable level.  Sividual protection measures, such as personal protective equipment  Personal protection equipment should be chosen according to the CEN standards and in the control of the CEN standards a			
* - For sampling details, please see the source document.  Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)  Material  Value  Determinant  Specimen  Sampling Time  Chromium Selenide (CrSe)  150 µg/l  Selen  Serum  *  (CAS 12053-13-3)  * - For sampling details, please see the source document.  commended monitoring ocedures  rived no effect levels Not available.  Not available.  Not available.  Sexposure controls  propriate engineering introls  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation to be matched to conditions. If applicable, use process enclosures, local exhaust ventilation engineering controls to maintain airborne levels below recommended exposure limits. If limits have not been established, maintain airborne levels to an acceptable level.  dividual protection measures, such as personal protective equipment  Personal protection equipment should be chosen according to the CEN standards and in the constant of the center	Cromo total Urine *	25 μg/l	
Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)  Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe) 150 μg/l Selen Serum *  (CAS 12053-13-3)  * - For sampling details, please see the source document.  commended monitoring occlures  rived no effect levels NELs)  edicted no effect no effect no effect no entrations (PNECs)  Exposure controls propriate engineering ntrols  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation engineering controls to maintain airborne levels below recommended exposure limits. If a policial protection measures, such as personal protective equipment  General information  Personal protection equipment should be chosen according to the CEN standards and in the control of the co	Cromo total Offic	• =	* Face and the solution of the St. of the St.
Material Value Determinant Specimen Sampling Time  Chromium Selenide (CrSe) 150 µg/l Selen Serum *  (CAS 12053-13-3)  * - For sampling details, please see the source document.  commended monitoring brocedures.  Follow standard monitoring procedures.  Not available.  Not available.  Not available.  Setum *  Follow standard monitoring procedures.  Not available.  Not available.  Setum *  Follow standard monitoring procedures.  Follow standard monitoring procedures.  Setum *  Follow standard monitoring procedures.  Follow standard monitoring procedures.  Setum *  Follow standard monitoring procedures.			, , , ,
(CAS 12053-13-3)  * - For sampling details, please see the source document.  commended monitoring forcedures.  Follow standard monitoring procedures.  Not available.  Not available.  Not available.  Sedicted no effect propriate engineering forcedures for monitoring procedures.  Cappage for the commended monitoring procedures.  Sedicted no effect propriate engineering forcedures for monitoring procedures.  Cappage for the commended engineering for monitoring procedures.  Sedicted no effect propriate engineering for available.  Sedicted no effect propriate engineering	Determinant Specimen Sampling Time	Value	Material
Follow standard monitoring procedures.  Follow standard monitoring procedures.  Not available.  Not available.  Not available.  Not available.  Sedicted no effect propriate engineering procedures propriate engineering natrols  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation to be matched to conditions. If applicable, use process enclosures, local exhaust ventilation engineering controls to maintain airborne levels below recommended exposure limits. If a limits have not been established, maintain airborne levels to an acceptable level.  Sedicted no effect procedures.  Not available.	Selen Selen		(CAS 12053-13-3)
Not available.  Sedicted no effect necentrations (PNECs)  Sedicted no effect necentration (typically 10 air changes per hour) should be used. Ventilation repaired necentration necentrations (PNECs)  Sedicted no effect necentration (PNECs)  Sed			
Acticed no effect notentrations (PNECs)  2. Exposure controls  Propriate engineering be matched to conditions. If applicable, use process enclosures, local exhaust ventilation engineering controls to maintain airborne levels below recommended exposure limits. If limits have not been established, maintain airborne levels to an acceptable level.  General information  Not available.  Sood general ventilation (typically 10 air changes per hour) should be used. Ventilation regimeering controls to maintain airborne levels below recommended exposure limits. If a limits have not been established, maintain airborne levels to an acceptable level.  General information  Personal protection equipment should be chosen according to the CEN standards and in the control of the central protection equipment should be chosen according to the central protect	oring procedures.	FOIIOW Standard me	
Cood general ventilation (typically 10 air changes per hour) should be used. Ventilation reprivate engineering be matched to conditions. If applicable, use process enclosures, local exhaust ventilation engineering controls to maintain airborne levels below recommended exposure limits. If a limits have not been established, maintain airborne levels to an acceptable level.  Idividual protection measures, such as personal protective equipment  General information  Personal protection equipment should be chosen according to the CEN standards and in the control of the CEN standards and in the control of the central of		Not available.	
Good general ventilation (typically 10 air changes per hour) should be used. Ventilation reportance be matched to conditions. If applicable, use process enclosures, local exhaust ventilation engineering controls to maintain airborne levels below recommended exposure limits. If a limits have not been established, maintain airborne levels to an acceptable level.  dividual protection measures, such as personal protective equipment  General information  Personal protection equipment should be chosen according to the CEN standards and in the conditions. If applicable, use process enclosures, local exhaust ventilation reports to maintain airborne levels below recommended exposure limits. If a limit have not been established, maintain airborne levels to an acceptable level.		Not available.	
be matched to conditions. If applicable, use process enclosures, local exhaust ventilation engineering controls to maintain airborne levels below recommended exposure limits. If a limits have not been established, maintain airborne levels to an acceptable level.  dividual protection measures, such as personal protective equipment  General information  Personal protection equipment should be chosen according to the CEN standards and in a limit of the CEN standards are limit of the center of the			. Exposure controls
<b>General information</b> Personal protection equipment should be chosen according to the CEN standards and in	ons. If applicable, use process enclosures, local exhaust ventilation, or other or maintain airborne levels below recommended exposure limits. If exposure	be matched to con- engineering contro	
with the supplier of the personal protective equipment.	quipment should be chosen according to the CEN standards and in discussion	Personal protection	_
<b>Eye/face protection</b> If contact is likely, safety glasses with side shields are recommended.			Evo/face weeks-ti

- Hand protection For prolonged or repeated skin contact use suitable protective gloves.

- Other Wear suitable protective clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. **Respiratory protection** 

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

**Hygiene measures** Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

**Environmental exposure** 

controls

Contain spills and prevent releases and observe national regulations on emissions. Environmental

manager must be informed of all major releases.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

**Appearance** 

Physical state Solid. Solid. **Form** 

Colour Not available. Odour Not available. **Odour threshold** Not available. Not available. Melting point/freezing point Not available. Initial boiling point and Not available.

boiling range

Not available. Flash point Not available. **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

< 0,0000001 kPa at 25 °C Vapour pressure

Vapour density Not available. Relative density Not available.

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available. (n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** Not available. Not available. **Explosive properties** Not available. Oxidising properties

9.2. Other information

**Molecular formula** CrSe

# **SECTION 10: Stability and reactivity**

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous No hazardous decomposition products are known.

decomposition products

# **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

#### Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. **Eye contact** Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

**Symptoms** Exposure may cause temporary irritation, redness, or discomfort.

## 11.1. Information on toxicological effects

**Acute toxicity** No data available.

Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Serious eye damage/eye

irritation

Due to partial or complete lack of data the classification is not possible. Respiratory sensitisation Skin sensitisation Due to partial or complete lack of data the classification is not possible. Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible. Carcinogenicity Due to partial or complete lack of data the classification is not possible.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Chromium Selenide (CrSe) (CAS 12053-13-3)

## IARC Monographs. Overall Evaluation of Carcinogenicity

Chromium Selenide (CrSe) (CAS 12053-13-3) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible. Specific target organ toxicity Due to partial or complete lack of data the classification is not possible.

- single exposure

Specific target organ toxicity

- repeated exposure

Due to partial or complete lack of data the classification is not possible.

**Aspiration hazard** Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

Other information Not available.

# **SECTION 12: Ecological information**

12.1. Toxicity Very toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

12.2. Persistence and

degradability

No data is available on the degradability of this product.

12.3. Bioaccumulative

potential

No data available.

**Partition coefficient** 

Not available.

n-octanol/water (log Kow)

**Bioconcentration factor (BCF)** Not available. 12.4. Mobility in soil No data available.

12.5. Results of PBT and

vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and methods/information

its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Special precautions

Dispose in accordance with all applicable regulations.

# **SECTION 14: Transport information**

**ADR** 

14.1. - 14.6.: Not regulated as dangerous goods.

**RID** 

14.1. - 14.6.: Not regulated as dangerous goods.

**ADN** 

14.1. - 14.6.: Not regulated as dangerous goods.

TATA

14.1. - 14.6.: Not regulated as dangerous goods.

**IMDG** 

14.1. - 14.6.: Not regulated as dangerous goods.

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **EU** regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Chromium Selenide (CrSe) (CAS 12053-13-3)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

# **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

#### **Restrictions on use**

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Chromium Selenide (CrSe) (CAS 12053-13-3)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

#### Other EU regulations

# Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Chromium Selenide (CrSe) (CAS 12053-13-3)

Other regulations The product is classified and labelled in accordance with EC directives or respective national laws.

> This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. This product is not in compliance with Directive 2002/95/EC on the restriction of the use of certain

hazardous substances in electrical and electronics equipment (RoHS).

**National regulations** Follow national regulation for work with chemical agents.

**15.2. Chemical safety assessment** 

No Chemical Safety Assessment has been carried out.

# **SECTION 16: Other information**

**List of abbreviations**Not available. **References**Not available.

**Training information** Follow training instructions when handling this material.

**Disclaimer** The information in the sheet was written based on the best knowledge and experience currently

available.

Material name: Chromium Selenide (CrSe)

1HC Version #: 03 Revision date: 10-January-2018 Issue date: 02-September-2014