



**MATERION**

Product name: Beryllium Solid

# CHEMICAL PRODUCT SAFETY DATA SHEET

Prepared in accordance with GB/T 16483 and GB/T 17519.

Issue date: 07-16-2015  
Revision date: 05-10-2024  
Version #: 04  
SDS No: M10

## SECTION 1 Chemical product and company identification

Chinese name of chemical	固敏
English name of chemical	Beryllium Solid
Synonyms	Metallic Beryllium, Glucinium, I220H, IF-1®, S200F, S200FH, S200FC, SR200, S65, PS-200®, PF10, PF-60®, O-30, O-30H, I-70, I-70H, UHP Beryllium, .9999 Beryllium, B-26D, Be, IS-50M®
Manufacturer/Supplier	Materion Brush Inc.
Address	6070 Parkland Boulevard Mayfield Heights, OH 44124 United States
Contact person	Product Stewardship Director
Telephone	+1.216.383.4019
e-mail	Materion-PS@materion.com
Emergency telephone number	+1.216.383.4019
Issue date	07-16-2015
Revision date	05-10-2024
Supersedes date	05-04-2021
SDS No	M10

## SECTION 2 Hazards identification

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

### Emergency overview

Causes damage to organs through prolonged or repeated exposure. May cause cancer. Prolonged exposure may cause chronic effects. The material as sold in solid form is generally not considered hazardous. However, if the process involves grinding, melting, cutting or any other process that causes a release of dust or fumes, hazardous levels of airborne particulate could be generated.

### GHS hazard categories

Physical hazards	Not classified.	
Health hazards	Carcinogenicity Specific target organ toxicity, repeated exposure	Category 1 Category 1 (Respiratory system)
Environmental hazards	Not classified.	

### Label elements

#### Pictograms



#### Signal word

Danger

#### Hazard statement

H350	May cause cancer.
H372	Causes damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.

**Precautionary statement****Prevention**

P201	Minimize dust generation and accumulation.
P202	Obtain special instructions before use.
P260	Do not handle until all safety precautions have been read and understood.
P280	Do not breathe dust/fume.
	Wear protective gloves/protective clothing/eye protection/face protection.

**Response**

P302 + P350	If on skin: Wash with plenty of water.
P363	Wash contaminated clothing before reuse.
P304 + P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P342 + P311	If experiencing respiratory symptoms: Call a poison center/doctor.
P308 + P313	If exposed or concerned: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

**Safety storage**

P405	Store locked up.
------	------------------

**Disposal**

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

**Physical and chemical hazards**

No unusual fire or explosion hazards noted.

**Health hazards**

Prolonged inhalation may be harmful.

**Environmental hazards**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Supplemental information**

Exposure to the elements listed in Section 3 by inhalation, ingestion, and skin contact can occur when melting, casting, dross handling, pickling, chemical cleaning, heat treating, abrasive cutting, welding, grinding, sanding, polishing, milling, crushing, or otherwise heating or abrading the surface of this material in a manner which generates particulate.

For further information, please contact the Product Stewardship Department at +1.216.383.4019.

**SECTION 3 Composition/information on ingredients**

Substance/mixture	Substance	Concentration (%)	CAS Number
铍		100	7440-41-7
Beryllium			

**SECTION 4 First aid measures**

<b>Inhalation</b>	If symptoms develop move victim to fresh air. For breathing difficulties, oxygen may be necessary. Breathing difficulty caused by inhalation of particulate requires immediate removal to fresh air. If breathing has stopped, perform artificial respiration and obtain medical help.
<b>Skin contact</b>	Take off contaminated clothing and wash before reuse. Thoroughly wash skin cuts or wounds to remove all particulate debris from the wound. Seek medical attention for wounds that cannot be thoroughly cleansed. Treat skin cuts and wounds with standard first aid practices such as cleansing, disinfecting and covering to prevent wound infection and contamination before continuing work. Obtain medical help for persistent irritation. Material accidentally implanted or lodged under the skin must be removed.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention if symptoms persist.
<b>Ingestion</b>	If swallowed, seek medical advice immediately and show this container or label. Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person.
<b>Most important symptoms and health effects</b>	May cause allergic skin reaction. May cause allergic respiratory reaction. Prolonged exposure may cause chronic effects.

<b>Personal protection for first-aid responders</b>	If exposed or concerned: get medical attention/advice. Wash contaminated clothing before reuse. As supplied, there is no immediate medical risk with beryllium products in article form. First aid measures provided are related to particulate containing beryllium.
<b>Notes to physician</b>	<p>Treatment of Chronic Beryllium Disease: There is no known treatment which will cure chronic beryllium disease. Prednisone or other corticosteroids are the most specific treatment currently available. They are directed at suppressing the immunological reaction and can be effective in diminishing signs and symptoms of chronic beryllium disease. In cases where steroid therapy has had only partial or minimal effectiveness, other immunosuppressive agents, such as cyclophosphamide, cyclosporine, or methotrexate, have been used. In view of the potential side effects of all the immunosuppressive medications, including steroids such as prednisone, they should be used only under the direct care of a physician. Other treatment, such as oxygen, inhaled steroids or bronchodilators, may be prescribed by some physicians and can be effective in selected cases. In general, treatment is reserved for cases with significant symptoms and/or significant loss of lung function. The decision about when and with what medication to treat is a judgment situation for individual physicians.</p> <p>In their 2014 official statement on the Diagnosis and Management of Beryllium Sensitivity and Chronic Beryllium Disease, the American Thoracic Society states that "it seems prudent for workers with BeS to avoid all future occupational exposure to beryllium."</p> <p>The effects of continued low exposure to beryllium are unknown for individuals who are sensitized to beryllium or who have a diagnosis of chronic beryllium disease. It is generally recommended that persons who are sensitized to beryllium or who have CBD terminate their occupational exposure to beryllium.</p>

## SECTION 5 Fire-fighting measures

<b>Extinguishing media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. The product is non-combustible.
<b>Extinguishing media to avoid</b>	Do not use water to extinguish fires around operations involving molten metal due to the potential for steam explosions.
<b>Specific hazards</b>	During fire, gases hazardous to health may be formed.
<b>Special fire fighting procedures</b>	Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Water runoff can cause environmental damage. Do not use water to extinguish fires around operations involving molten metal due to the potential for steam explosions.
<b>Protection of fire-fighters</b>	Firefighters should wear full protective clothing including self contained breathing apparatus. Wear suitable protective equipment.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.
<b>Specific methods</b>	Pressure-demand self-contained breathing apparatus must be worn by firefighters or any other persons potentially exposed to the particulate released during or after a fire.

## SECTION 6 Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	
<b>For non-emergency personnel</b>	Wear appropriate personal protective equipment.
<b>For emergency responders</b>	Keep unnecessary personnel away. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Environmental precautions</b>	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
<b>Clean-up methods and materials and containment measures</b>	Clean up in accordance with all applicable regulations. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
<b>Prevention of secondary hazards</b>	Not available.

## SECTION 7 Handling and storage

<b>Handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Do not breathe dust/fume. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Wear respiratory protection. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices.
<b>Storage</b>	Keep locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## SECTION 8 Exposure controls/personal protection

### Exposure limits

#### Occupational Exposure Limits for Hazardous Agents in the Workplace, Chemical Hazardous Agents (GBZ 2.1-2019)

Material	Type	Value
Beryllium (CAS 7440-41-7)	PC-STEL	0.001 mg/m <sup>3</sup>
	PC-TWA	0.0005 mg/m <sup>3</sup>

**Biological limit values** No biological exposure limits noted for the ingredient(s).

### Exposure guidelines

#### China OELs. Occupational Exposure Limits for Hazardous Agents in the Workplace, Chemical Hazardous Agents (GBZ 2.1-2007): Skin designation

Beryllium and compounds, as Be (CAS 7440-41-7) Can be absorbed through the skin.

**Monitoring methods**

**VENTILATION:** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Ensure adequate ventilation, especially in confined areas.

Whenever possible, the use of local exhaust ventilation or other engineering controls is the preferred method of controlling exposure to airborne particulate. Where utilized, exhaust inlets to the ventilation system must be positioned as close as possible to the source of airborne generation. Avoid disruption of the airflow in the area of a local exhaust inlet by equipment such as a man-cooling fan. Check ventilation equipment regularly to ensure it is functioning properly. Provide training on the use and operation of ventilation to all users. Use qualified professionals to design and install ventilation systems.

**WET METHODS:** Machining operations are usually performed under a liquid lubricant/coolant flood which assists in reducing airborne particulate. However, the cycling through of machine coolant containing finely divided particulate in suspension can result in the concentration building to a point where the particulate may become airborne during use. Certain processes such as sanding and grinding may require complete hooded containment and local exhaust ventilation. Prevent coolant from splashing onto floor areas, external structures or operators' clothing. Utilize a coolant filtering system to remove particulate from the coolant.

**WORK PRACTICES:** Develop work practices and procedures that prevent particulate from coming in contact with worker skin, hair, or personal clothing. If work practices and/or procedures are ineffective in controlling airborne exposure or visual particulate from deposition on skin, hair, or clothing, provide appropriate cleaning/washing facilities. Procedures should be written that clearly communicate the facility's requirements for protective clothing and personal hygiene. These clothing and personal hygiene requirements help keep particulate from being spread to non-production areas or from being taken home by the worker. Never use compressed air to clean work clothing or other surfaces.

Fabrication processes may leave a residue of particulate on the surface of parts, products or equipment that could result in employee exposure during subsequent material handling activities. As necessary, clean loose particulate from parts between processing steps. As a standard hygiene practice, wash hands before eating or smoking.

**HOUSEKEEPING:** Use vacuum and wet cleaning methods for particulate removal from surfaces. Be certain to de-energize electrical systems, as necessary, before beginning wet cleaning. Use vacuum cleaners with high efficiency particulate air (HEPA). Do not use compressed air, brooms, or conventional vacuum cleaners to remove particulate from surfaces as this activity can result in elevated exposures to airborne particulate. Follow the manufacturer's instructions when performing maintenance on HEPA filtered vacuums used to clean hazardous materials. Follow standard monitoring procedures.

Fabrication processes may leave a residue of particulate on the surface of parts, products or equipment that could result in employee exposure during subsequent material handling activities.

**Engineering measures**

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Whenever possible, the use of local exhaust ventilation or other engineering controls is the preferred method of controlling exposure to airborne particulate. Where utilized, exhaust inlets to the ventilation system must be positioned as close as possible to the source of airborne generation. Avoid disruption of the airflow in the area of a local exhaust inlet by equipment such as a man-cooling fan. Check ventilation equipment regularly to ensure it is functioning properly. Provide training on the use and operation of ventilation to all users. Use qualified professionals to design and install ventilation systems.

**Personal protective equipment****Respiratory protection**

When airborne exposures exceed or have the potential to exceed the occupational exposure limits, approved respirators must be used as specified by an Industrial Hygienist or other qualified professional. Respirator users must be medically evaluated to determine if they are physically capable of wearing a respirator. Quantitative and/or qualitative fit testing and respirator training must be satisfactorily completed by all personnel prior to respirator use. Users of tight fitting respirators must be clean shaven on those areas of the face where the respirator seal contacts the face. Use pressure-demand airline respirators when performing jobs with high potential exposures such as changing filters in a baghouse air cleaning device.

**Hand protection**

Wear gloves to prevent contact with particulate or solutions. Wear gloves to prevent metal cuts and skin abrasions during handling.

**Eye protection**

Wear approved safety glasses, goggles, face shield and/or welder's helmet when risk of eye injury is present, particularly during operations that generate dust, mist or fume.

**Skin and body protection**

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Protective overgarments or work clothing must be worn by persons who may become contaminated with particulate during activities. Skin contact with this material may cause, in some sensitive individuals, an allergic dermal response. Particulate that becomes lodged under the skin has the potential to induce sensitization and skin lesions.

**SECTION 9 Physical and chemical properties****Appearance**

<b>Physical state</b>	Solid.
<b>Form</b>	Solid. Various shapes.
<b>Color</b>	Grey
<b>Odor</b>	None.
<b>Odor threshold</b>	Not applicable.
<b>pH</b>	Not applicable
<b>Melting point/freezing point</b>	2348.6 °F (1287 °C)
<b>Boiling point, initial boiling point, and boiling range</b>	5378 °F (2970 °C)
<b>Flash point</b>	Not applicable
<b>Explosive limit - lower (%)</b>	Not applicable.
<b>Explosive limit - upper (%)</b>	Not applicable.
<b>Vapor pressure</b>	6.67 hPa estimated
<b>Vapor density</b>	Not applicable
<b>Relative density</b>	Not applicable.
<b>Density</b>	1.85 g/cm <sup>3</sup> 2 estimated
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not applicable.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not applicable.
<b>Decomposition temperature</b>	Not applicable.
<b>Evaporation rate</b>	Not applicable.
<b>Flammability (solid, gas)</b>	Not available.
<b>Other data</b>	
<b>Explosive properties</b>	Not explosive.
<b>Molecular formula</b>	Be
<b>Molecular weight</b>	9.01 g/mol
<b>Oxidizing properties</b>	Not oxidizing.
<b>Specific gravity</b>	1.85 estimated

**Viscosity** Not applicable.

## SECTION 10 Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Stability** Material is stable under normal conditions.

**Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.

**Conditions to avoid** Contact with incompatible materials. Avoid dust formation. Contact with acids. Contact with alkalis.

**Incompatible materials** Acids. Caustics. Chlorinated hydrocarbons. Strong acids, alkalies and oxidizing agents.

**Hazardous decomposition products** No hazardous decomposition products are known.

## SECTION 11 Toxicological information

**Acute toxicity** Based on available data, the classification criteria are not met.

**Routes of exposure** Inhalation.

**Symptoms** Prolonged exposure may cause chronic effects. Coughing.

**Skin corrosion/irritation** Not likely, due to the form of the product.

**Serious eye damage/eye irritation** Not likely, due to the form of the product.

**Respiratory or skin sensitization**

**Respiratory sensitization** May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Skin sensitizer** Not a skin sensitizer.

**Germ cell mutagenicity** Due to lack of data the classification is not possible.

**Carcinogenicity** Cancer hazard.

### China OELs for hazardous agents in the workplace: Carcinogen Category

Beryllium and compounds, as Be (CAS 7440-41-7) Carcinogenic to humans.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Beryllium (CAS 7440-41-7) 1 Carcinogenic to humans.

**Toxic to reproduction** Not classified.

**Specific target organ toxicity following single exposure** Not classified.

**Specific target organ toxicity following repeated exposure** May cause damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.

**Aspiration hazard** Due to lack of data the classification is not possible.

**Chronic effects** Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

**Other information** Symptoms may be delayed.

## SECTION 12 Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulation** No data available.

**Mobility in soil** No data available.

**Other hazardous effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## SECTION 13 Disposal considerations

**Residual waste** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.
<b>Local disposal regulations</b>	Material should be recycled if possible. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

## SECTION 14 Transport information

### CNDG

Not regulated as dangerous goods.

### IATA

Not regulated as dangerous goods.

### IMDG

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

## SECTION 15 Regulatory information

### Law of the People's Republic of China on Prevention and Control of Occupational Diseases

#### Classification of occupational disease hazards

Beryllium and its compounds (CAS 7440-41-7)

### Regulations on the Control over Safety of Dangerous Chemicals

#### Catalog of Hazardous Chemicals

Beryllium powder (CAS 7440-41-7)

### Regulations on Labor Protection in Workplaces Where Toxic Substances Are Used

#### Directory of Highly Toxic Substances

Beryllium (CAS 7440-41-7)

### Provision on the Environmental Administration of New Chemical Substances

#### China Inventory of Existing Chemical Substances

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

<b>Other regulations</b>	This safety data sheet conforms to the following laws, regulations and standards: Measures for the Safe Use of Chemicals in Workplaces General Rules for Preparation of Precautionary Labels for Chemicals (GB15258-2009 ) Regulations on Labor Protection in Workplaces Where Toxic Products Are Used Packing Symbol of Dangerous Goods(GB190-2009) Regulations on the Control over Safety of Dangerous Chemicals Safety Data Sheet for Chemical Products - Content and Order of Sections (GB/T 16483-2008) Packing - Pictorial Marking for Handling of Goods (GB/T191-2008)
--------------------------	--

### China. National Catalogue of Hazardous Wastes

Beryllium (CAS 7440-41-7)

### International regulations

#### Stockholm Convention

Not applicable.

#### Rotterdam Convention

Not applicable.

#### Montreal Protocol

Not applicable.

**Kyoto protocol**

Not applicable.

**Basel Convention**

Not applicable.

**SECTION 16 Other information****References**

EPA: AQUIRE database  
GB6944-2012: Classification and Code of Dangerous Goods.  
GB12268-2012: List of Dangerous Goods.  
NLM: Hazardous Substances Data Base  
US. IARC Monographs on Occupational Exposures to Chemical Agents

**Further information**

Transportation Emergency  
Call Chemtrec at:  
US: 800.424.9300  
International: 703.741.5970  
Spain: 900.868.538  
Switzerland: 0800.564.402  
Chemtrec's toll free, mobile-enabled number in Germany – 0800 1817059  
South Korea Toll-free Number – 080-880-0468

**Disclaimer**

This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.

**Revision information**

This document has undergone significant changes and should be reviewed in its entirety.