



**MATERION**

# SAFETY DATA SHEET

## 1. Identification

Product identifier	AlBeCast™ 930 and 940
Other means of identification	
SDS number	M36
Synonyms	Aluminum Beryllium Matrix, Cast Aluminum-Beryllium Alloy
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Company name	Materion Brush Inc.
Address	6070 Parkland Boulevard Mayfield Heights, OH 44124 United States
Telephone	.216.383.4019
Website	www.materion.com
E-mail	Materion-PS@materion.com
Contact person	Product Stewardship Director
Emergency phone number	.216.383.4019

## 2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Sensitization, respiratory	Category 1
	Sensitization, skin	Category 1
	Carcinogenicity	Category 1
	Specific target organ toxicity, repeated exposure	Category 1 (Respiratory system)
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

### Label elements



Signal word Danger

Hazard statement May cause an allergic skin reaction. Causes damage to organs (respiratory system) through prolonged or repeated exposure by inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause cancer.

### Precautionary statement

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Do not breathe dust/fume. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

#### Response

If on skin: Wash with plenty of water. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center/doctor. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention.

#### Storage

Store locked up.

<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	Exposure to the elements listed in Section 3 by inhalation, ingestion, and skin contact can occur when melting, casting, dross handling, pickling, chemical cleaning, heat treating, abrasive cutting, welding, grinding, sanding, polishing, milling, crushing, or otherwise heating or abrading the surface of this material in a manner which generates particulate.
	For further information, please contact the Product Stewardship Department at +1.216.383.4019.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Beryllium		7440-41-7	48 - 55
Aluminum		7429-90-5	36 - 42
Silicon		7440-21-3	3 - 5
Nickel		7440-02-0	2 - 5
Silver		7440-22-4	1.5 - 4
Cobalt		7440-48-4	0 - 3

### 4. First-aid measures

<b>Inhalation</b>	If symptoms develop move victim to fresh air. For breathing difficulties, oxygen may be necessary. Breathing difficulty caused by inhalation of particulate requires immediate removal to fresh air. If breathing has stopped, perform artificial respiration and obtain medical help.
<b>Skin contact</b>	Take off contaminated clothing and wash before reuse. Thoroughly wash skin cuts or wounds to remove all particulate debris from the wound. Seek medical attention for wounds that cannot be thoroughly cleansed. Treat skin cuts and wounds with standard first aid practices such as cleansing, disinfecting and covering to prevent wound infection and contamination before continuing work. Obtain medical help for persistent irritation. Material accidentally implanted or lodged under the skin must be removed.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention if symptoms persist.
<b>Ingestion</b>	If swallowed, seek medical advice immediately and show this container or label. Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person.
<b>Most important symptoms/effects, acute and delayed</b>	May cause allergic skin reaction. May cause allergic respiratory reaction. Prolonged exposure may cause chronic effects.

**Indication of immediate medical attention and special treatment needed**

Treatment of Chronic Beryllium Disease: There is no known treatment which will cure chronic beryllium disease. Prednisone or other corticosteroids are the most specific treatment currently available. They are directed at suppressing the immunological reaction and can be effective in diminishing signs and symptoms of chronic beryllium disease. In cases where steroid therapy has had only partial or minimal effectiveness, other immunosuppressive agents, such as cyclophosphamide, cyclosporine, or methotrexate, have been used. In view of the potential side effects of all the immunosuppressive medications, including steroids such as prednisone, they should be used only under the direct care of a physician. Other treatment, such as oxygen, inhaled steroids or bronchodilators, may be prescribed by some physicians and can be effective in selected cases. In general, treatment is reserved for cases with significant symptoms and/or significant loss of lung function. The decision about when and with what medication to treat is a judgment situation for individual physicians.

In their 2014 official statement on the Diagnosis and Management of Beryllium Sensitivity and Chronic Beryllium Disease, the American Thoracic Society states that "it seems prudent for workers with BeS to avoid all future occupational exposure to beryllium."

The effects of continued low exposure to beryllium are unknown for individuals who are sensitized to beryllium or who have a diagnosis of chronic beryllium disease. It is generally recommended that persons who are sensitized to beryllium or who have CBD terminate their occupational exposure to beryllium.

**General information**

If exposed or concerned: get medical attention/advice. Get medical attention if symptoms occur. Wash contaminated clothing before reuse. As supplied, there is no immediate medical risk with beryllium products in massive form. First aid measures provided are related to particulate containing beryllium.

**5. Fire-fighting measures**

**Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. The product is non-combustible.

**Unsuitable extinguishing media**

Do not use water to extinguish fires around operations involving molten metal due to the potential for steam explosions.

**Specific hazards arising from the chemical**

During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters**

Firefighters should wear full protective clothing including self contained breathing apparatus. Wear suitable protective equipment.

**Fire fighting equipment/instructions**

Move containers from fire area if you can do so without risk. Water runoff can cause environmental damage. Do not use water to extinguish fires around operations involving molten metal due to the potential for steam explosions.

**Specific methods**

Pressure-demand self-contained breathing apparatus must be worn by firefighters or any other persons potentially exposed to the particulate released during or after a fire.

**General fire hazards**

No unusual fire or explosion hazards noted.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. In solid form this material poses no special clean-up problems.

**Methods and materials for containment and cleaning up**

The product is immiscible with water and will spread on the water surface. Clean up in accordance with all applicable regulations. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. The product is insoluble in water.

**Environmental precautions**

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Do not breathe dust/fume. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Wear respiratory protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Keep locked-up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Avoid contact with acids and alkalis. Avoid contact with oxidizing agents.

## 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components	Type	Value
Beryllium (CAS 7440-41-7)	STEL	0.002 mg/m3
	TWA	0.0002 mg/m3

#### US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Cobalt (CAS 7440-48-4)	PEL	0.1 mg/m3	Dust and fume.
Nickel (CAS 7440-02-0)	PEL	1 mg/m3	
Silicon (CAS 7440-21-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Silver (CAS 7440-22-4)	PEL	0.01 mg/m3	

#### US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Silicon (CAS 7440-21-3)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

#### US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Beryllium (CAS 7440-41-7)	TWA	0.00005 mg/m3 (as beryllium)	Inhalable fraction.
Cobalt (CAS 7440-48-4)	TWA	0.02 mg/m3	Inhalable fraction.
Nickel (CAS 7440-02-0)	TWA	1.5 mg/m3	Inhalable fraction.
Silver (CAS 7440-22-4)	TWA	0.1 mg/m3	Dust and fume.

**NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended**

Components	Type	Value
Beryllium (CAS 7440-41-7)	IDLH	4 mg/m3
Cobalt (CAS 7440-48-4)	IDLH	20 mg/m3
Nickel (CAS 7440-02-0)	IDLH	10 mg/m3
Silver (CAS 7440-22-4)	IDLH	10 mg/m3

**US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)**

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	5 mg/m3	Welding fume or pyrophoric powder.
		5 mg/m3	Respirable.
		10 mg/m3	Total
Cobalt (CAS 7440-48-4)	TWA	0.05 mg/m3	Dust and fume.
Nickel (CAS 7440-02-0)	TWA	0.015 mg/m3	
Silicon (CAS 7440-21-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Silver (CAS 7440-22-4)	TWA	0.01 mg/m3	Dust.

**US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants**

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	PEL	5 mg/m3	Welding fume.
		5 mg/m3	Respirable fraction.
		5 mg/m3	Pyrophoric powder.
		10 mg/m3	Total dust.
Beryllium (CAS 7440-41-7)	Ceiling	0.025 mg/m3 (as beryllium)	
	PEL	0.0002 (as beryllium)	
	STEL	0.002 mg/m3	
	TWA	0.0001 mg/m3	
Cobalt (CAS 7440-48-4)	PEL	0.02 mg/m3	Dust and fume.
Nickel (CAS 7440-02-0)	PEL	0.5 mg/m3	
Silicon (CAS 7440-21-3)	PEL	5 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Silver (CAS 7440-22-4)	PEL	0.01 mg/m3	

**Biological limit values****ACGIH Biological Exposure Indices (BEI)**

Components	Value	Determinant	Specimen	Sampling Time
Cobalt (CAS 7440-48-4)	15 µg/l	Cobalt	Urine	*
Nickel (CAS 7440-02-0)	5 µg/l	Nickel	Urine	*

\* - For sampling details, please see the source document.

## Exposure guidelines

On July 14, 2020, the Occupational Safety and Health Administration (OSHA) issued the final Beryllium Standard for General Industry (29 CFR 1910.1024) which includes a Permissible Exposure Limit (PEL) of 0.2 µg/m<sup>3</sup> as an 8-hour TWA. The Preamble to the OSHA Beryllium Standards in 29 CFR Parts 1910, 1915 and 1926 states: "OSHA concludes that exposure to beryllium constitutes a significant risk of material impairment to health and that the final rule will substantially lower that risk. The Agency considers the level of risk remaining at the new TWA PEL to still be significant. However, OSHA did not adopt a lower TWA PEL because the Agency could not demonstrate technological feasibility of a lower TWA PEL. The Agency has adopted the STEL and ancillary provisions of the rule to further reduce the remaining significant risk."

Based on joint research conducted with the National Institute for Occupational Safety and Health (NIOSH), Materion adopted an 8 element Beryllium Worker Protection Model (BWPM) which includes the use of a recommended exposure guideline (REG) for airborne beryllium of 0.2 µg/m<sup>3</sup> as a time-weighted average (TWA) limit for an 8-hour work day. Subsequent NIOSH studies have shown that the BWPM has reduced but not eliminated the risk of beryllium sensitization and chronic beryllium disease (CBD) in workers. Therefore, Materion recommends that beryllium users not only comply with the OSHA Beryllium Standard and carefully apply all elements of the BWPM, but reduce airborne exposures to the lowest feasible level. Information on the BWPM can be found at [www.berylliumsafety.com](http://www.berylliumsafety.com) or by contacting Materion at +1 800.862.4118.

The American Conference of Governmental Industrial Hygienists (ACGIH®) is a scientific body that has developed guidelines for all listed substances. In its development documents, the ACGIH® states that "Threshold Limit Values and Biological Exposure Indices represent conditions under which ACGIH® believes that nearly all workers may be repeatedly exposed without adverse health effects. They are not fine lines between safe and dangerous exposures, nor are they a relative index of toxicology."

Specific genetic factors have been identified and shown to increase an individual's susceptibility to CBD. Medical testing is available to detect those genetic factors in individuals.

**Appropriate engineering controls**      **VENTILATION:** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Whenever possible, the use of local exhaust ventilation or other engineering controls is the preferred method of controlling exposure to airborne particulate. Where utilized, exhaust inlets to the ventilation system must be positioned as close as possible to the source of airborne generation. Avoid disruption of the airflow in the area of a local exhaust inlet by equipment such as a man-cooling fan. Check ventilation equipment regularly to ensure it is functioning properly. Provide training on the use and operation of ventilation to all users. Use qualified professionals to design and install ventilation systems.

**WET METHODS:** Machining operations are usually performed under a liquid lubricant/coolant flood which assists in reducing airborne particulate. However, the cycling through of machine coolant containing finely divided particulate in suspension can result in the concentration building to a point where the particulate may become airborne during use. Certain processes such as sanding and grinding may require complete hooded containment and local exhaust ventilation. Prevent coolant from splashing onto floor areas, external structures or operators' clothing. Utilize a coolant filtering system to remove particulate from the coolant.

**WORK PRACTICES:** Develop work practices and procedures that prevent particulate from coming in contact with worker skin, hair, or personal clothing. If work practices and/or procedures are ineffective in controlling airborne exposure or visual particulate from deposition on skin, hair, or clothing, provide appropriate cleaning/washing facilities. Procedures should be written that clearly communicate the facility's requirements for protective clothing and personal hygiene. These clothing and personal hygiene requirements help keep particulate from being spread to non-production areas or from being taken home by the worker. Never use compressed air to clean work clothing or other surfaces.

Fabrication processes may leave a residue of particulate on the surface of parts, products or equipment that could result in employee exposure during subsequent material handling activities. As necessary, clean loose particulate from parts between processing steps. As a standard hygiene practice, wash hands before eating or smoking.

**HOUSEKEEPING:** Use vacuum and wet cleaning methods for particulate removal from surfaces. Be certain to de-energize electrical systems, as necessary, before beginning wet cleaning. Use vacuum cleaners with high efficiency particulate air (HEPA). Do not use compressed air, brooms, or conventional vacuum cleaners to remove particulate from surfaces as this activity can result in elevated exposures to airborne particulate. Follow the manufacturer's instructions when performing maintenance on HEPA filtered vacuums used to clean hazardous materials.

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Wear approved safety glasses, goggles, face shield and/or welder's helmet when risk of eye injury is present, particularly during operations that generate dust, mist or fume.
<b>Skin protection</b>	
<b>Hand protection</b>	Wear gloves to prevent contact with particulate or solutions. Wear gloves to prevent metal cuts and skin abrasions during handling.
<b>Other</b>	Protective overgarments or work clothing must be worn by persons who may become contaminated with particulate during activities. Skin contact with this material may cause, in some sensitive individuals, an allergic dermal response. Particulate that becomes lodged under the skin has the potential to induce sensitization and skin lesions.

<b>Respiratory protection</b>	When airborne exposures exceed or have the potential to exceed the occupational exposure limits, approved respirators must be used as specified by an Industrial Hygienist or other qualified professional. Respirator users must be medically evaluated to determine if they are physically capable of wearing a respirator. Quantitative and/or qualitative fit testing and respirator training must be satisfactorily completed by all personnel prior to respirator use. Users of tight fitting respirators must be clean shaven on those areas of the face where the respirator seal contacts the face. Use pressure-demand airline respirators when performing jobs with high potential exposures such as changing filters in a baghouse air cleaning device.
-------------------------------	---

<b>Thermal hazards</b>	Not applicable.
------------------------	-----------------

<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice.
---------------------------------------	--

## 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	Solid.
<b>Form</b>	Solid. Various shapes.
<b>Color</b>	Grey.

<b>Odor</b>	None.
-------------	-------

<b>Odor threshold</b>	Not applicable.
-----------------------	-----------------

<b>pH</b>	Not applicable.
-----------	-----------------

<b>Melting point/freezing point</b>	1220 °F (660 °C) estimated / Not applicable.
-------------------------------------	--

<b>Initial boiling point and boiling range</b>	Not applicable.
--	-----------------

<b>Flash point</b>	Not applicable.
--------------------	-----------------

<b>Evaporation rate</b>	Not applicable.
-------------------------	-----------------

<b>Flammability (solid, gas)</b>	None known.
----------------------------------	-------------

### Upper/lower flammability or explosive limits

<b>Explosive limit - lower (%)</b>	Not applicable.
------------------------------------	-----------------

<b>Explosive limit - upper (%)</b>	Not applicable.
------------------------------------	-----------------

<b>Vapor pressure</b>	Not applicable.
-----------------------	-----------------

<b>Vapor density</b>	Not applicable.
----------------------	-----------------

<b>Relative density</b>	Not applicable.
-------------------------	-----------------

### Solubility(ies)

<b>Solubility (water)</b>	Insoluble.
---------------------------	------------

<b>Partition coefficient (n-octanol/water)</b>	Not applicable.
--	-----------------

<b>Auto-ignition temperature</b>	Not applicable.
----------------------------------	-----------------

<b>Decomposition temperature</b>	Not applicable.
----------------------------------	-----------------

<b>Viscosity</b>	Not applicable.
------------------	-----------------

### Other information

<b>Density</b>	2.62 g/cm3 estimated
----------------	----------------------

<b>Explosive properties</b>	Not explosive.
-----------------------------	----------------

<b>Oxidizing properties</b>	Not oxidizing.
-----------------------------	----------------

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
-------------------	---

<b>Chemical stability</b>	Material is stable under normal conditions.
---------------------------	---

<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
---	--

<b>Conditions to avoid</b>	Contact with incompatible materials. Avoid dust formation. Contact with acids. Contact with alkalis.
----------------------------	--



**Incompatible materials** Caustics. Chlorinated hydrocarbons. Chlorine. Fluorine. Strong acids, alkalies and oxidizing agents.

**Hazardous decomposition products** No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** May cause sensitization by inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful. May cause damage to organs (respiratory system) through prolonged or repeated exposure.

**Skin contact** May cause an allergic skin reaction.

**Eye contact** Harmful in contact with eyes.

**Ingestion** Toxic if swallowed.

**Symptoms related to the physical, chemical and toxicological characteristics** Coughing. Difficulty in breathing. May cause an allergic skin reaction. Dermatitis. Rash. Respiratory disorder.

### Information on toxicological effects

**Acute toxicity** May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction.

Components	Species	Test Results
Silicon (CAS 7440-21-3)		
<u>Acute</u>		
<b>Oral</b>		
LD50	Rat	3160 mg/kg

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Not classified.

**Serious eye damage/eye irritation** Harmful in contact with eyes.

### Respiratory or skin sensitization

#### ACGIH sensitization

Cobalt and inorganic compounds, inhalable fraction, as Co (CAS 7440-48-4)

Dermal sensitization

Respiratory sensitization

**Respiratory sensitization** May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** Cancer hazard.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Beryllium (CAS 7440-41-7)	1 Carcinogenic to humans.
Cobalt (CAS 7440-48-4)	2B Possibly carcinogenic to humans.
Nickel (CAS 7440-02-0)	2B Possibly carcinogenic to humans.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Beryllium (CAS 7440-41-7)	Cancer
---------------------------	--------

### US. National Toxicology Program (NTP) Report on Carcinogens

Beryllium (CAS 7440-41-7)	Known To Be Human Carcinogen.
Cobalt (CAS 7440-48-4)	Reasonably Anticipated to be a Human Carcinogen.
Nickel (CAS 7440-02-0)	Known To Be Human Carcinogen.
	Reasonably Anticipated to be a Human Carcinogen.

<b>Reproductive toxicity</b>	Not classified.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.
<b>Aspiration hazard</b>	Not an aspiration hazard.
<b>Chronic effects</b>	Hazardous by OSHA criteria. Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.
<b>Further information</b>	Symptoms may be delayed.

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product			Species	Test Results
AlBeCast™ 930 and 940				
Aquatic				
Acute				
Crustacea	EC50	Daphnia	0.2375 mg/l, 48 hours estimated	
Fish	LC50	Fish	0.0511 mg/l, 96 hours estimated	
Components			Species	Test Results
Aluminum (CAS 7429-90-5)				
Aquatic				
Acute				
Fish	LC50	Grass carp, white amur (Ctenopharyngodon idella)	0.21 - 0.31 mg/l, 96 hours	
Nickel (CAS 7440-02-0)				
Aquatic				
Acute				
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.06 mg/l, 4 days	
Silver (CAS 7440-22-4)				
Aquatic				
Acute				
Fish	LC50	Fathead minnow (Pimephales promelas)	0.0019 - 0.003 mg/l, 96 hours	

\* Estimates for product may be based on additional component data not shown.

<b>Persistence and degradability</b>	No data is available on the degradability of this product.
<b>Bioaccumulative potential</b>	No data available.
<b>Mobility in soil</b>	No data available.
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

<b>Disposal instructions</b>	Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations. Material should be recycled if possible. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal. When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	D011: Waste Silver The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

<b>DOT</b>	Not regulated as dangerous goods.
<b>IATA</b>	Not regulated as dangerous goods.
<b>IMDG</b>	Not regulated as dangerous goods.

## 15. Regulatory information

<b>US federal regulations</b>	All components are on the U.S. EPA TSCA Inventory List. This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
-------------------------------	---

### Toxic Substances Control Act (TSCA)

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### CERCLA Hazardous Substance List (40 CFR 302.4)

Beryllium (CAS 7440-41-7)	Listed.
Cobalt (CAS 7440-48-4)	Listed.
Nickel (CAS 7440-02-0)	Listed.
Silver (CAS 7440-22-4)	Listed.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Beryllium (CAS 7440-41-7)	Cancer lung effects (CBD and acute beryllium disease) beryllium sensitization respiratory tract irritation
---------------------------	---

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

<b>SARA 311/312 Hazardous chemical</b>	No (Exempt)
--	-------------

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Aluminum	7429-90-5	36 - 42
Beryllium	7440-41-7	48 - 55
Cobalt	7440-48-4	0 - 3
Nickel	7440-02-0	2 - 5
Silver	7440-22-4	1.5 - 4

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Beryllium (CAS 7440-41-7)

Cobalt (CAS 7440-48-4)

Nickel (CAS 7440-02-0)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)**

Contains component(s) regulated under the Safe Drinking Water Act.

**US state regulations**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Aluminum (CAS 7429-90-5)

Beryllium (CAS 7440-41-7)

Cobalt (CAS 7440-48-4)

Silver (CAS 7440-22-4)

**California Proposition 65**

**WARNING:** This product can expose you to chemicals including Beryllium, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Beryllium (CAS 7440-41-7)

Listed: October 1, 1987

Cobalt (CAS 7440-48-4)

Listed: July 1, 1992

Nickel (CAS 7440-02-0)

Listed: October 1, 1989

**16. Other information, including date of preparation or last revision**

Issue date 05-31-2015

Revision date 05-31-2024

Version # 06

**Further information**

Transportation Emergency

Call Chemtrec at:

US: 800.424.9300

International: 703.741.5970

Spain: 900.868.538

Switzerland: 0800.564.402

Chemtrec's toll free, mobile-enabled number in Germany – 0800 1817059

South Korea Toll-free Number – 080-880-0468

**Disclaimer**

This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.

**Revision information**

This document has undergone significant changes and should be reviewed in its entirety.