SAFETY DATA SHEET

1. Identification

Product identifier Magnesium Oxide-Zinc Oxide (MgO-ZnO)

Other means of identification

SDS number MKE-0280

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Not available.
Address Not available.
Telephone Not available.
E-mail Not available.
Emergency phone number Not available.

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment, Category 2

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word None.

Hazard statement Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Avoid release to the environment.

Response Collect spillage.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 81.67% of the mixture consists of component(s) of unknown acute oral toxicity. 100% of the

mixture consists of component(s) of unknown acute dermal toxicity. 81.67% of the mixture consists of component(s) of unknown acute inhalation toxicity. 81.67% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 81.67% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

For further information, please contact the Product Stewardship Department at +1.800.862.4118.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Magnesium Oxide		1309-48-4	0 - 81.67
Zinc oxide		1314-13-2	0 - 18.33

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists. Eye contact Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

Dusts may irritate the respiratory tract, skin and eyes. Coughing.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment

needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Specific hazards arising from

the chemical

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Methods and materials for containment and cleaning up Avoid the generation of dusts during clean-up. Collect dust using a vacuum cleaner equipped with HEPA filter. Prevent product from entering drains. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Handling and storage

Precautions for safe handling

Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Material name: Magnesium Oxide-Zinc Oxide (MgO-ZnO)

SDS US 1769 Version #: 02 Revision date: 10-13-2017 Issue date: 07-09-2015

8. Exposure controls/personal protection

Occupational exposure limits

US. USHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.100)	S. OSHA Table Z-1 Limits for Air Contaminants (2	(29 CFR 1910.1000)
--	--	--------------------

Components	Туре	Value	Form
Magnesium Oxide (CAS 1309-48-4)	PEL	15 mg/m3	Total particulate.
Zinc oxide (CAS 1314-13-2)	PEL	5 mg/m3	Respirable fraction.
,		5 mg/m3	Fume.
		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR	1910.1000)	_	
Components	Туре	Value	Form
Magnesium Oxide (CAS 1309-48-4)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Va	alues		
Components	Туре	Value	Form
Magnesium Oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.
Zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to 0		g,	
Components	Туре	Value	Form
Zinc oxide (CAS 1314-13-2)	0 "	15 mg/m3	Dust.
Zinc oxide (CAS 1314-13-2)	Ceiling	10 1119/1110	Daot.
Zinc oxide (CAS 1314-13-2)	Ceiling STEL	10 mg/m3	Fume.
Zinc oxide (CAS 1314-13-2)	-	-	
Zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Fume.
	STEL TWA	10 mg/m3 5 mg/m3 5 mg/m3	Fume. Dust.
	STEL	10 mg/m3 5 mg/m3 5 mg/m3	Fume. Dust.
US. California Code of Regula Components Magnesium Oxide (CAS	STEL TWA itions, Title 8, Section 5155. Airborne Con	10 mg/m3 5 mg/m3 5 mg/m3 taminants	Fume. Dust. Fume.
US. California Code of Regula Components Magnesium Oxide (CAS 1309-48-4)	STEL TWA tions, Title 8, Section 5155. Airborne Con Type PEL	10 mg/m3 5 mg/m3 5 mg/m3 taminants Value 10 mg/m3	Fume. Dust. Fume. Form
US. California Code of Regula Components Magnesium Oxide (CAS	STEL TWA tions, Title 8, Section 5155. Airborne Con- Type PEL PEL	10 mg/m3 5 mg/m3 5 mg/m3 taminants Value 10 mg/m3 5 mg/m3	Fume. Dust. Fume. Form Fume.
US. California Code of Regula Components Magnesium Oxide (CAS 1309-48-4) Zinc oxide (CAS 1314-13-2)	STEL TWA Itions, Title 8, Section 5155. Airborne Cont Type PEL PEL STEL	10 mg/m3 5 mg/m3 5 mg/m3 taminants Value 10 mg/m3 5 mg/m3 10 mg/m3	Fume. Dust. Fume. Form Fume. Fume.
US. California Code of Regula Components Magnesium Oxide (CAS 1309-48-4) Zinc oxide (CAS 1314-13-2) ogical limit values	STEL TWA Itions, Title 8, Section 5155. Airborne Cont Type PEL PEL STEL No biological exposure limits noted for the	10 mg/m3 5 mg/m3 5 mg/m3 taminants Value 10 mg/m3 5 mg/m3 10 mg/m3 he ingredient(s).	Fume. Dust. Fume. Form Fume. Fume. Fume. Fume.
US. California Code of Regula Components Magnesium Oxide (CAS 1309-48-4) Zinc oxide (CAS 1314-13-2)	STEL TWA Itions, Title 8, Section 5155. Airborne Cont Type PEL PEL STEL	10 mg/m3 5 mg/m3 5 mg/m3 taminants Value 10 mg/m3 5 mg/m3 10 mg/m3 ne ingredient(s). In changes per hour) should licable, use process enclosure airborne levels below recoved, maintain airborne levels into maintain concentration table respiratory protection in the late of the may generate dusts, us	Fume. Dust. Fume. Form Fume. Fume. Fume. be used. Ventilation rates ares, local exhaust ventilation mmended exposure limits. If to an acceptable level. s of dust particulates below the must be worn. If material is e appropriate local exhaust
US. California Code of Regula Components Magnesium Oxide (CAS 1309-48-4) Zinc oxide (CAS 1314-13-2) ogical limit values	STEL TWA Ations, Title 8, Section 5155. Airborne Contents Type PEL PEL STEL No biological exposure limits noted for the Good general ventilation (typically 10 air should be matched to conditions. If applior other engineering controls to maintain exposure limits have not been established if engineering measures are not sufficient Occupational Exposure Limit (OEL), suit ground, cut, or used in any operation where	10 mg/m3 5 mg/m3 5 mg/m3 taminants Value 10 mg/m3 5 mg/m3 10 mg/m3 ne ingredient(s). In changes per hour) should licable, use process enclosure airborne levels below recoved, maintain airborne levels into maintain concentration table respiratory protection in the late of the may generate dusts, us	Fume. Dust. Fume. Form Fume. Fume. Fume. be used. Ventilation rates ares, local exhaust ventilation mmended exposure limits. If to an acceptable level. s of dust particulates below the must be worn. If material is e appropriate local exhaust
US. California Code of Regula Components Magnesium Oxide (CAS 1309-48-4) Zinc oxide (CAS 1314-13-2) ogical limit values propriate engineering controls	STEL TWA Attions, Title 8, Section 5155. Airborne Contact Type PEL PEL STEL No biological exposure limits noted for the Good general ventilation (typically 10 air should be matched to conditions. If applied or other engineering controls to maintain exposure limits have not been established if engineering measures are not sufficient Occupational Exposure Limit (OEL), suit ground, cut, or used in any operation whe ventilation to keep exposures below the	10 mg/m3 5 mg/m3 5 mg/m3 taminants Value 10 mg/m3 5 mg/m3 10 mg/m3 he ingredient(s). If changes per hour) should incide	Fume. Dust. Fume. Form Fume. Fume. Fume. be used. Ventilation rates ares, local exhaust ventilation mmended exposure limits. If to an acceptable level. s of dust particulates below the must be worn. If material is e appropriate local exhaust
US. California Code of Regula Components Magnesium Oxide (CAS 1309-48-4) Zinc oxide (CAS 1314-13-2) Togical limit values Propriate engineering controls atrol parameters vidual protection measures, such	STEL TWA Ations, Title 8, Section 5155. Airborne Contage PEL PEL STEL No biological exposure limits noted for the Good general ventilation (typically 10 air should be matched to conditions. If applie or other engineering controls to maintain exposure limits have not been established If engineering measures are not sufficien Occupational Exposure Limit (OEL), suit ground, cut, or used in any operation who ventilation to keep exposures below the Follow standard monitoring procedures. Ch as personal protective equipment	10 mg/m3 5 mg/m3 5 mg/m3 taminants Value 10 mg/m3 5 mg/m3 10 mg/m3 ne ingredient(s). If changes per hour) should licable, use process enclosure airborne levels below recoved, maintain airborne levels into maintain concentration table respiratory protection in the may generate dusts, us recommended exposure linear goggles).	Fume. Dust. Fume. Form Fume. Fume. Fume. be used. Ventilation rates ares, local exhaust ventilation mmended exposure limits. If to an acceptable level. s of dust particulates below the must be worn. If material is e appropriate local exhaust
US. California Code of Regula Components Magnesium Oxide (CAS 1309-48-4) Zinc oxide (CAS 1314-13-2) ogical limit values propriate engineering controls atrol parameters vidual protection measures, successed by the control of the	STEL TWA Ations, Title 8, Section 5155. Airborne Contype PEL PEL STEL No biological exposure limits noted for the Good general ventilation (typically 10 airs should be matched to conditions. If applie or other engineering controls to maintain exposure limits have not been established if engineering measures are not sufficient Occupational Exposure Limit (OEL), suit ground, cut, or used in any operation whe ventilation to keep exposures below the Follow standard monitoring procedures. Chas personal protective equipment Wear safety glasses with side shields (owe was appropriate chemical resistant glocal descriptions.)	10 mg/m3 5 mg/m3 5 mg/m3 taminants Value 10 mg/m3 5 mg/m3 10 mg/m3 ne ingredient(s). If changes per hour) should licable, use process enclosure airborne levels below recoved, maintain airborne levels into maintain concentration table respiratory protection in the may generate dusts, us recommended exposure linear goggles).	Fume. Dust. Fume. Form Fume. Fume. Fume. be used. Ventilation rates ares, local exhaust ventilation mmended exposure limits. If to an acceptable level. s of dust particulates below that the must be worn. If material is e appropriate local exhaust
US. California Code of Regula Components Magnesium Oxide (CAS 1309-48-4) Zinc oxide (CAS 1314-13-2) ogical limit values propriate engineering controls atrol parameters vidual protection measures, sur Eye/face protection	STEL TWA Ations, Title 8, Section 5155. Airborne Contype PEL PEL STEL No biological exposure limits noted for the Good general ventilation (typically 10 air should be matched to conditions. If applie or other engineering controls to maintain exposure limits have not been established if engineering measures are not sufficien Occupational Exposure Limit (OEL), suit ground, cut, or used in any operation who ventilation to keep exposures below the Follow standard monitoring procedures. Ch as personal protective equipment Wear safety glasses with side shields (or	10 mg/m3 5 mg/m3 5 mg/m3 taminants Value 10 mg/m3 5 mg/m3 10 mg/m3 ne ingredient(s). In changes per hour) should licable, use process enclosure airborne levels below recoved, maintain airborne levels not to maintain concentration table respiratory protection in the may generate dusts, us recommended exposure linear goggles).	Fume. Dust. Fume. Form Fume. Fume. Fume. be used. Ventilation rates ares, local exhaust ventilation mmended exposure limits. If to an acceptable level. s of dust particulates below must be worn. If material is e appropriate local exhaust hits.

Material name: Magnesium Oxide-Zinc Oxide (MgO-ZnO)

SDS US

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Powder.
Color Not available.
Odor Not available.
Odor threshold Not available.

pH Not available.Melting point/freezing point 3587 °F (1975 °C) estimated

Initial boiling point and boiling

range

6512 °F (3600 °C) estimated

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.00001 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 3.95 g/cm3 estimated

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 3.95 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Contact with incompatible materials.

Incompatible materials Phosphorus. Chlorine.

Material name: Magnesium Oxide-Zinc Oxide (MgO-ZnO)

1769 Version #: 02 Revision date: 10-13-2017 Issue date: 07-09-2015 4 /

Hazardous decomposition

No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation Dust may irritate respiratory system. Prolonged inhalation may be harmful.

Skin contact Dust or powder may irritate the skin.

Eye contact Dust may irritate the eyes.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Dusts may irritate the respiratory tract, skin and eyes. Coughing.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

Zinc oxide (CAS 1314-13-2)

Acute

Inhalation

LC50 Mouse > 5.7 mg/l, 4 Hours

Oral

LD50 Mouse 7950 mg/kg

Rat > 5 g/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

Not classified.

repeated exposure

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Material name: Magnesium Oxide-Zinc Oxide (MgO-ZnO)

1769 Version #: 02 Revision date: 10-13-2017 Issue date: 07-09-2015 5 /

^{*} Estimates for product may be based on additional component data not shown.

Product Species Test Results

Magnesium Oxide-Zinc Oxide (MgO-ZnO)

Aquatic

Fish LC50 Fish 12253.1367 mg/l, 96 hours estimated

Components Species Test Results

Zinc oxide (CAS 1314-13-2)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 2246 mg/l, 96 hours

Persistence and degradabilityNo data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN3077

UN proper shipping name

Transport hazard class(es)

Environmentally hazardous substances, solid, n.o.s.

Class 9
Subsidiary risk Label(s) 9
Packing group III

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Special provisions 8, 146, 335, A112, B54, IB8, IP3, N20, T1, TP33

Packaging exceptions 155
Packaging non bulk 213
Packaging bulk 240

IATA

UN number UN3077

UN proper shipping name Environmentally hazardous substance, solid, n.o.s. **Transport hazard class(es)**

Class 9
Subsidiary risk Packing group III
Environmental hazards No.

^{*} Estimates for product may be based on additional component data not shown.

ERG Code 9L

Special precautions for user

Other information

Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN3077

UN proper shipping name Transport hazard class(es) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.


Class 9
Subsidiary risk cking group III

Packing group
Environmental hazards

Marine pollutant No. EmS F-A, S-F

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

DOT; IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Listed.

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Zinc oxide (CAS 1314-13-2)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Zinc oxide	1314-13-2	0 - 18.33

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material

is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Magnesium Oxide (CAS 1309-48-4)

16. Other information, including date of preparation or last revision

 Issue date
 07-09-2015

 Revision date
 10-13-2017

Version # 02

Disclaimer

cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.

8 / 8

1769 Version #: 02 Revision date: 10-13-2017 Issue date: 07-09-2015