



SAFETY DATA SHEET

MATERION

1. Identification

Product identifier Aluminum-Silicon powder

Other means of identification

SDS number 1AZ

Materion Code 1AZ

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Materion Electronic Materials
Address 6070 Parkland Blvd
Mayfield Heights, Ohio 44124
United States

Telephone 1.216.383.4019

E-mail Materion-PS@materion.com

Contact person Product Stewardship Director

Emergency phone number See Section 16

2. Hazard(s) identification

Physical hazards Substances and mixtures which, in contact with water, emit flammable gases Category 3

Health hazards Serious eye damage/eye irritation Category 2B

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 1

Hazardous to the aquatic environment, long-term hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement In contact with water releases flammable gas. Causes damage to organs (respiratory system) through prolonged or repeated exposure. Very toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Handle under inert gas. Protect from moisture. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response Get medical advice/attention if you feel unwell.

Storage Store in a dry place. Store in a closed container.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information For further information, please contact the Product Stewardship Department at +1.800.862.4118.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aluminum		7429-90-5	2 - 99
Silicon		7440-21-3	1 - 98

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Coughing. Discomfort in the chest. Shortness of breath. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Powder. Dry sand.
Unsuitable extinguishing media	Water. Do not use water jet as an extinguisher, as this will spread the fire. Carbon dioxide (CO ₂).
Specific hazards arising from the chemical	In contact with water releases flammable gas.
Special protective equipment and precautions for firefighters	Wear suitable protective equipment.
Fire fighting equipment/instructions	Do not get water inside container. Water runoff can cause environmental damage.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	In contact with water releases flammable gas.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Do not get water on spilled substance or inside containers. Collect spillage. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Large Spills: Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Small Spills: Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Handle under inert gas. Protect from moisture. Avoid contact with eyes. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a dry place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
Silicon (CAS 7440-21-3)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Silicon (CAS 7440-21-3)	TWA	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	1 mg/m ³	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	5 mg/m ³	Respirable.
		5 mg/m ³	Welding fume or pyrophoric powder.
		10 mg/m ³	Total
Silicon (CAS 7440-21-3)	TWA	5 mg/m ³	Respirable.
		10 mg/m ³	Total

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	PEL	5 mg/m ³	Pyrophoric powder.
		5 mg/m ³	Respirable fraction.
		5 mg/m ³	Welding fume.
		10 mg/m ³	Total dust.
Silicon (CAS 7440-21-3)	PEL	5 mg/m ³	Respirable fraction.
		10 mg/m ³	Total dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear suitable protective clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Solid.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	1220 °F (660 °C) estimated
Initial boiling point and boiling range	4220.6 °F (2327 °C) estimated
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	-0.01 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	2.52 g/cm ³ estimated
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	2.52 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Exposure to moisture. Contact with water liberates flammable gas. Moisture. Contact with incompatible materials.
Incompatible materials	Water. Chlorine. Fluorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Due to lack of data the classification is not possible.
Eye contact	Causes eye irritation.
Ingestion	Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics
Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Coughing. Discomfort in the chest. Shortness of breath.

Information on toxicological effects

Acute toxicity Not known.

Components	Species	Test Results
-------------------	----------------	---------------------

Silicon (CAS 7440-21-3)

Acute

Oral

LD50	Rat	3160 mg/kg
------	-----	------------

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Due to lack of data the classification is not possible.

Serious eye damage/eye irritation Causes eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Due to lack of data the classification is not possible.

Skin sensitization Due to lack of data the classification is not possible.

Germ cell mutagenicity Due to lack of data the classification is not possible.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Due to lack of data the classification is not possible.

Specific target organ toxicity - single exposure Due to lack of data the classification is not possible.

Specific target organ toxicity - repeated exposure Causes damage to organs () through prolonged or repeated exposure.

Aspiration hazard	Due to lack of data the classification is not possible.
Chronic effects	Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Product	Species	Test Results
Aluminum-Silicon powder		
Aquatic		
<i>Acute</i>		
Fish	LC50 Fish	0.2121 mg/l, 96 hours estimated
Components	Species	Test Results
Aluminum (CAS 7429-90-5)		
Aquatic		
<i>Acute</i>		
Fish	LC50 Grass carp, white amur (Ctenopharyngodon idella)	0.21 - 0.31 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN number	UN1398
UN proper shipping name	Aluminum silicon powder, uncoated
Transport hazard class(es)	
Class	4.3
Subsidiary risk	-
Label(s)	4.3
Packing group	III
Environmental hazards	
Marine pollutant	No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Special provisions A1, A19, IB8, IP4, T1, TP33
Packaging exceptions 151
Packaging non bulk 213
Packaging bulk 241

IATA

UN number UN1398
UN proper shipping name Aluminum silicon powder, uncoated
Transport hazard class(es)
 Class 4.3
 Subsidiary risk -
 Label(s) 4.3
Packing group III
Environmental hazards Yes
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1398
UN proper shipping name Aluminum silicon powder, uncoated, MARINE POLLUTANT
Transport hazard class(es)
 Class 4.3
 Subsidiary risk -
 Label(s) 4.3
Packing group III
Environmental hazards
 Marine pollutant Yes
EmS Not assigned.
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.


DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

All components are on the U.S. EPA TSCA Inventory List.
This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
CERCLA/SARA Hazardous Substances - Not applicable.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

Classified hazard categories

In contact with water emits flammable gas
Serious eye damage or eye irritation

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Aluminum	7429-90-5	2 - 99

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Aluminum (CAS 7429-90-5)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

16. Other information, including date of preparation or last revision

Issue date 05-27-2015
Revision date 04-08-2024
Version # 06
Further information Transportation Emergency
Call Chemtrec at:
US: 800.424.9300
International: 703.741.5970
Spain: 900.868.538
Switzerland: 0800.564.402
Chemtrec's toll free, mobile-enabled number in Germany – 0800 1817059
South Korea Toll-free Number – 080-880-0468

Disclaimer This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.

Revision information This document has undergone significant changes and should be reviewed in its entirety.